



Superior Performance Unique Microemulsion Coolant

KOOLRite 2290 is a new generation of oil-based cutting fluid that utilizes JTM's unique **BioArmor Technology** to give you a coolant with outstanding control of bacteria without the use of bactericides. With BioArmor protection, KOOLRite 2290 will **stop sump odors**, give you exceptionally long sump life and a clean, comfortable, safe work environment for machine operators.

KOOLRite 2290 does not contain chlorine or sulfur and yet with the use of new technology, it is designed for on all metals and operations including heavy duty operations on tough alloys where extreme pressure is required.



Unlike competitive oil-based coolants, KOOLRite 2290 will reject tramp oils allowing clean coolant to be delivered to the chip/tool interface keeping your machine tool clean with a minimum of residual film, while providing excellent corrosion control.

KOOLRite 2290 ADVANTAGES

Praised in the Shop

No sump stench!

Lowest possible coolant consumption

At least doubles your sump life!

No biocides needed

Low foam and multi-metal capability simplifies coolant inventory

Minimizes machine maintenance and downtime

Low total costs

Non-staining formula, great for all aluminum alloys

Greatest Operator Comfort; Welcome at Home

No sump stench!

No additions of biocides to the sump

Non-hazardous formula

Does not contain phenols, nitrites, chlorine, bactericides or DCHA

Proven gentle on hands!

Unique BioArmor™ Technology



BioArmor Technology means built-in resistance to bacterial growth without the use of bactericides. Only KOOLRite has it!



KOOLRite Formulation Does Not Support Bacterial Growth



Competitive Soluble Oil Teems with Bacteria

THE KOOLRite CHALLENGE:

KOOLRite 2290 will provide twice the sump life than the soluble oil you presently use or your purchase is **FREE!**

Recommended Starting Dilutions

Operations	Iron & Carbon Steel	High Alloy & Stainless Steels	Tool Steels	Aluminum	Copper Alloys
Grinding	4% to 5%	4% to 6%	5% to 6%	5% to 7%	4% to 5%
Milling, Drilling, Turning, Cut-off, Sawing, Screw Machining	5% to 7%	7% to 8%	6% to 8%	5% to 7%	5% to 7%
Tapping, Reaming, Broaching and Form Milling	5% to 7%	8% to 10%	8% to 10%	8% to 10%	5% to 7%

Directions for Use

The sump life of this coolant, as with any other coolant, will be greatly enhanced if charged to a clean system. You can utilize JTM's Sump Cleaner to disinfect your sump. KOOLRite 2290 can be metered through automatic dispensing systems available from JTM. Contact your representative regarding cleaning procedures and dispensers.

Always add the KOOLRite 2290 concentrate to the water and not the water to the concentrate. Proper maintenance in removing extraneous oils is beneficial for extended coolant life. The concentration can be monitored by refractive index.

Refractive Index1.3 (Refractive reading x 1.3 = % of concentration of dilution)

Product Data

Appearance:

Concentrate Opaque Amber
@ 10% Dilution Milky

pH (concentrate): 9.3

pH (10% dilution): 9.1

Density (lbs/gal): 8.3

Recommended Metals

Aluminum Alloys	Cast Iron
Nodular Iron	Carbon Steel
Tool Steel	High Alloy Steel
Stainless Steel	Titanium
High Ni Steel	Copper Alloys

The perfect coolant for central system. Will eliminate odors and the need for additives, and will lower coolant consumption 15% to 25%.



Quality Industrial Lubricants
for Over 100 Years.

www.koolrite.net
email: sales@koolrite.net
phone: 440-287-2302
fax: 440-287-3095
toll free: 800-229-6744

Material Safety Data Sheets are available for all products. All reasonable care has been taken to ensure that the above information is accurate as of the date of printing.

JTM Products, Inc. offers a complete line of Chemicals and Lubricants for Industry. Call us at 800-229-6744